



Product Service

# CERTIFICATE

No. Z1A 114659 0007 Rev. 00

**Holder of Certificate:** **Four Design ApS**  
Lucernemarken 17-19  
5260 Odense S  
DENMARK

**Certification Mark:**



**Product:** **Visitor chairs**  
**Swivel chairs for general use**

**Tested according to:** DIN EN 16139:2014  
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713231545

**Valid until:** 2027-03-15

**Date,** 2022-03-17

( Ulrich Sommer )

ZERTIFIKAT ◆ CERTIFICATE ◆ 認 證 證 書 ◆ CERTIFICADO ◆ CERTIFICAT

# CERTIFICATE

No. Z1A 114659 0007 Rev. 00

**Model(s):** **FourCast2 Wheeler /**  
**FourCast2 Wheeler Loop Armrest**  
  
**FourSure 66 /**  
**FourSure 66 Loop Armrests**

## Parameters:

<b>FourCast2 Wheeler / FourCast2 Wheeler Loop Armrest</b>	
Height backrest, lowest position [mm]	790
Height seat surface, lowest position [mm]	405
Height backrest, highest position [mm]	960
Height seat surface, highest position [mm]	575
Diameter [mm]	651.5
General description:	<ul style="list-style-type: none"> <li>- 5-star plastic base (PA6GF33), castor type "W" or "H", seat mechanism fixed or with permanent inclination</li> <li>- With or without armrests</li> <li>- Seat height adjustable by means of gas spring STAB-O-MAT "D"</li> <li>- Seat shell (5 – 10.5 mm, PP GS 40%)</li> <li>- Optional upholstered seat or seat/backrest cover</li> <li>- Seat mechanism made of steel tube Ø16x2 mm, flat steel 4 mm, connection welded, hand lever for seat height adjustment</li> <li>- Seat mechanism with permanent inclination: With pivoted gas spring taper made of aluminium die cast, end stop made of rubber</li> <li>- optional: writing tablet InnoTab</li> </ul>
<b>FourSure 66 / FourSure 66 Loop Armrests</b>	
Height backrest, lowest position [mm]	772
Height seat surface, lowest position [mm]	416
Height backrest, highest position [mm]	947
Height seat surface, highest position [mm]	591
Diameter [mm]	651.5
General description:	<ul style="list-style-type: none"> <li>- 5-star aluminium base, castors or glides</li> <li>- With or without armrests</li> <li>- Seat height adjustable by means of gas spring STAB-O-MAT "D"</li> <li>- Seat backrest shell (5 – 10.5 mm, PP GS 40%)</li> <li>- Optional upholstered seat or seat/backrest cover</li> <li>- Seat mechanism fixed or with permanent inclination: Made of steel tube Ø16x2 mm, flat steel 4 mm, connection welded, hand lever for seat height adjustment</li> <li>- Seat mechanism with permanent inclination: With pivoted gas spring taper made of aluminium die cast, end stop made of rubber</li> <li>- optional: writing tablet InnoTab</li> </ul>