

Test Report

Report Number:
883474-6



**DANISH
TECHNOLOGICAL
INSTITUTE**

Gregersensvej 1
DK-2630 Taastrup
+45 72 20 20 00
info@teknologisk.dk
www.teknologisk.dk

Page 1 of 3
Init.: JJU/JHA
Order no.: 883474
Encl.: 2

Assignor: Four Design A/S, Faaborgvej 14, DK-5854 Gislev

Item : FourSure® 105 - Also covers FourSure® 90

Sampling: The assignor confirms having selected the product. The product was forwarded by the assignor and received at Danish Technological Institute on 13 December 2019.

Period: The test took place from 31 December 2019 to 29 January 2020.

Method: EN 16139:2013, Furniture - Strength, durability and safety - Requirements for non domestic seating
EN 16139 Test severity L1: General use: E.g. in office buildings, showrooms, public halls, function rooms, cafés, restaurants, canteens, banks, bars.
Additional information is given in enclosure B.

Test results: **Passed.**
The results are shown in enclosure A.

Terms: This test was conducted accredited in accordance with international requirements (ISO/IEC 17025:2005) and in accordance with the General Terms and Conditions of Danish Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent.

Place: Danish Technological Institute, Taastrup, Building and Construction

Signature: This document is only valid with a digital signature from Danish Technological Institute.
Date of issue 29 January 2020.
Jesper Junge Pedersen
Consultant



DIGITALLY SIGNED DOCUMENT

DANISH TECHNOLOGICAL INSTITUTE



DANAK

TEST Reg.no. 2



Test of Model: FourSure® 105 - Also covers FourSure® 90

Loading according to test severity L1.

Test no.	Test	Test Method	Cycles	Load	Result
4.1	General	EN 16139, 4.1			Passed
4.2.2	Shear and squeeze points under influence of powered mechanisms	EN 16139, 4.2.2			N/A
4.2.3	Shear and squeeze points during use	EN 16139, 4.2.3			Passed
4.3.2	Swivelling chairs	EN 1335			N/A
4.3.3	Non swivelling chairs	EN 1022			Passed
4.4	Rolling resistance of the unloaded chair	EN 16139, 4.4			N/A
5	Strength and durability requirements	EN 16139, 5			Passed
6.1.1	Seat static load and back static load test	EN 1728, 6.4	10 10	Seat: 1600 N Back: 560 N	Passed
6.1.2	Seat front edge static load	EN 1728, 6.5	10	Seat: 1300 N	Passed
6.1.3	Vertical load on back rests	EN 1728, 6.6	10	Seat: 1300 N Back: 600 N	Passed
6.1.4	Foot rest static load test	EN 1728, 6.8	10	1300 N	Passed
6.1.4	Leg rest static load test	EN 1728, 6.9	10		N/A
6.1.5	Arm rest sideways static load test	EN 1728, 6.10	10		N/A
6.1.6	Arm rest downwards static load test	EN 1728, 6.11	5		N/A
6.1.7	Vertical upwards static load on arm rests	EN 1728, 6.13	10		N/A
6.1.8	Combined seat and back durability test	EN 1728, 6.17	100000 100000	Seat: 1000 N Back: 300 N	Passed
6.1.9	Seat front edge durability test	EN 1728, 6.18	50000	800 N	Passed
6.1.10	Arm rest durability test	EN 1728, 6.20	30000		N/A
6.1.11	Foot rest durability test	EN 1728, 6.21	50000	1000 N	Passed
6.1.12	Leg forward static load test	EN 1728, 6.15	10	Edge: 300 N (Seat: 1000 N)	Passed
6.1.13	Legs sideways static load test	EN 1728, 6.16	10	Edge: 250 N (Seat: 1000 N)	Passed
6.1.14	Seat impact test	EN 1728, 6.24	10	240 mm	Passed
6.1.15	Back impact test	EN 1728, 6.25	10	210 mm / 38 °	Passed
6.1.16	Arm Impact Test	EN 1728, 6.26	10		N/A
6.1.17	Drop test (multiple seating)	EN 1728, 6.27.1	2 x 5		N/A
6.1.18	Auxiliary writing surface static load test	EN 1728, 6.14			N/A
6.1.19	Auxiliary writing surface durability test	EN 1728, 6.22	10000		N/A
7	Information for use	EN 16139, 7			N/A



Information required by EN 16139:2013

European Standards used:

EN 16139:2013 - Furniture - Strength, durability and safety - Requirements for non-domestic seating

EN 1728/AC:2012 - Domestic furniture - Seating - Test methods - Determination of strength and durability

EN 1022:2005 - Domestic furniture - Seating - Determination of stability

EN 1335:2009 - Office furniture - Office work chair - Part 3: Test methods

Details of tested seating:

Model:	FourSure® 105 - Also covers FourSure® 90			Type:	Barstool		
Length:	450 mm	Depth:	550 mm	Height:	1095 mm	Weight:	7 kg
Materials:	Polypropylene - Base: Chrome						

Details of defects observed before testing:

None.

Details of any deviations from this standard:

None.

Any variation from the specified temperature range:

None.

Test result:

See appendix A.

Name and address of the test facility:

Danish Technological Institute, Gregersensvej, Taastrup 2630, Denmark

Date of test:

2019-12-31 to 2020-01-29

Photo of the received sample:

