

FourMe® 66

Design by Strand + Hvass



FourMe® 66

Design by Strand + Hvass

Product options

VARIATIONS

- Bio-polypropylene shell
- Seat pad
- Inside upholstery
- Fully upholstered

OPTIONAL

Gas lift including footring
Extra height gas lift including footring (585-845mm)
GS Certification

ACCESSORIES

Loose seat pad
Inno®Tab

UPHOLSTERY

Can be upholstered in a broad range of upholstery fabrics, from our upholstery collection. Please visit our price list for further information.

SHELL COLOUR



Ebony Black
NCS S 9000-N



Aqua
NCS S 4020-B



Anthracite
RAL 7015



Beach
NCS S 2502-Y

BASE



Black Polymid
Base



Black/Polished
Aluminium Base



Elevate comfort and flexibility with the FourMe® 66, a wheeled meeting room chair ideal for meetings and educational settings. Its design embodies functionality, aesthetics, and comfort, making it an ideal addition to any office or collaborative set up. Pair it with an Inno®tab table for added versatility.

Technical specifications

WEIGHT

Polypropylene shell, with gas:
7,5 kg

Seat pad, with gas:
8,4 kg

Inside upholstery, with gas:
7,9 kg

Fully upholstery, with gas:
8,1 kg

TEST

EN 16139:2013 - L1
AfPS GS 2019: 01 PAK

Materials

SHELL

Bio Composite: Wood Plastic Composite with wood fibre (min. 20 %).

FOAM & GLUE

CMHR-65H Foam and Glue (SABA Activator 3739, Aquabond RSD 3801 blue).

FOAM THICKNESS

Seat upholstery: 15 mm.
Inside upholstery: 15 mm.
Fully upholstery: 20/10/5 mm.

BASE

Base: PA (Nylon) and 30% Glass Fibre or painted aluminium and polished aluminium.
Gaslift standard:
St. 37, 410mm-585mm

UPHOLSTERY PROTECTION

ABS

CASTORS, STANDARD

Soft castors, free wheeling:
Ø50 mm, PA (Nylon) Type 6 and PUR.
Black (RAL 9005) and grey (RAL 7022).

CASTORS, OPTIONAL

Hard castors with unloaded brakes:
Ø50 mm, PA (Nylon) Type 6 and PUR.
Black (RAL 9005) and grey (RAL 7022).

Hard castors will be locked when not in use.

GS CERTIFICATION


Base Black metal, diam. 702mm

GS soft castors, brake unloaded:
Ø50 mm, Plastic, soft wheel
Black (RAL 9005) and grey (RAL 7022).


GS hard castors, Ø50 mm, brake unloaded:
Plastic, hard wheel
black - black (Ral 9005)

Dimensions


FourMe® 66
Polypropylene shell w. gas lift




FourMe® 66
Seat pad w. gas lift



FourMe® 66
Inside upholstery w. gas lift




FourMe® 66
Fully upholstery w. gas lift



Environmental data

Product environmental data can assist you in meeting the requirements for LEED, BREEAM, WELL, and SKA building certifications.


FOURME 66 BIO-PP SHELL WITH TILT



RECYCLED CONTENT




RECYCLABILITY



CARBON FOOTPRINT

85
Kg CO₂e per unit


MATERIAL BREAKDOWN




FOURME 66 BIO-PP SHELL SEAT PAD WITH TILT



RECYCLED CONTENT



RECYCLABILITY



CARBON FOOTPRINT

45
Kg CO₂e per unit


MATERIAL BREAKDOWN




FOURME 66 BIO-PP SHELL INNER UPHOLSTERED WITH TILT



RECYCLED CONTENT




RECYCLABILITY



CARBON FOOTPRINT

93
Kg CO₂e per unit


MATERIAL BREAKDOWN




FOURME 66 BIO-PP SHELL FULLY UPHOLSTERED WITH TILT



RECYCLED CONTENT




RECYCLABILITY



CARBON FOOTPRINT

120
Kg CO₂e per unit

MATERIAL BREAKDOWN



CARBON FOOTPRINT

The carbon footprint (CO₂e) covers the full product life cycle, cradle-to-grave. Calculations follow the Product Environmental Footprint (PEF) methodology and are obtained using the MALBAR screening tool.



UPHOLSTERY

Please note that fabric is not included in the above figures.

Quality and environment

At Ocee & Four Design, we care about sustainability. We strive to reduce our impact by producing quality furniture in a sustainable manner. Find out more about our journey on [Oceefour.com](https://oceefour.com) ↗

COMPANY CERTIFICATIONS
ISO 9001
ISO 14001
FSC Chain of Custody
(License Code: FSC-C161956) FISP Full Membership

WARRANTY

Ocee & Four Design provides a 5-year warranty on all products within our price list. This warranty covers breakage and damage of products occurring because of deficient craftsmanship performance under normal use. The warranty shall lapse if the product shows signs of mishandling abuse or other physical damage. The warranty does not cover those parts of the product which are exposed to abrasion during use.

INSTRUCTIONS

Assembly instructions can be found at our website.

MAINTENANCE

Refer to our [Maintenance Guide](#) ↗

DISASSEMBLY & RECYCLING

Products should be disassembled and separated into their components and materials before recycling. Most products can be disassembled using hand tools. Metal parts are commonly

recycled. Powder coated frames are treated with a paint classified as not dangerous according to directive 1999/45/EF. Wood can either be recycled or incinerated. Plastic shells can be recycled. Upholstery and veneer shells are not recyclable but can be disposed of through incineration. Processes for recycling vary so check with your waste management organisation.