FourSure® 66

Design by Strand + Hvass





FourSure® 66

Design by Strand + Hvass

Product options

VARIATIONS

- · Polypropylene shell
- Seat pad
- · Inside upholsterv
- · Fully upholstered

OPTIONAL

Loop armrest Extra height gas lift including footring (585-845mm) Hard castors with breakes **GS** Certification

ACCESSORIES

Inno®Tab Hook

UPHOLSTERY

Can be upholstered in a broad range of upholstery fabrics, from our upholstery collection. Please visit our price list for further information.



SHELL COLOUR





NCS S 5005-B80G

NCS S 5010-G70Y

Terracotta NCS S 4510-Y60R

NCS S 6005-Y10R

Aqua NCS S 4020-B





NCS S 2040-G80Y

Orange NCS S 2070-Y70R

Oriental Red

Jungle green NCS 4050-G40Y Introducing the FourSure® 66, an exceptional office swivel chair that brings a new level of comfort and adaptability to your workspace. Its elegant design and robust construction make it a perfect fit for collaborative working platforms. Whether in educational facilities, conference centers, or office settings, this chair stands out. Plus, when paired with Inno®Tab, you can effortlessly switch from lecture-mode to a collaborative setup in seconds. Say hello to simplified group work with this unique swivel chair.

BASE





Black Polymid

Aluminium Base



Technical specifications

WEIGHT

Polypropylene shell, with gas: 7,5 kg

Seat pad, with gas: 8 kg

Inside upholstery, with gas:

8,4 kg

Fully upholstery, with gas: 7,8kg

Polypropylene shell, with gas and loop armrest: 8,7 kg

TEST

EN 16139:2013 - L1 AfPS GS 2019: 01 PAK

Materials

SHELL

Polypropylene with reinforced glass fibre (Skin: 15%, core: 40%), recyclable.

FOAM & GLUE

CMHR-65H Foam and Glue (SABA Activator 3739, Aquabond RSD 3801 blue).

FOAM THICKNESS

Seat upholstery: 15 mm. Inside upholstery: 15 mm. Fully upholstery: 20/10/5 mm.

BASE

Base: PA (Nylon) and 30% Glass Fibre or painted aluminium and polished aluminium. Caslift standard: St. 37, 410mm-585mm

UPHOLSTERY PROTECTION

CASTORS, STANDARD

Soft castors, free wheeling: Ø50 mm, PA (Nylon) Type 6 and PUR. Black (RAL 9005) and grey (RAL 7022).

CASTORS, OPTIONAL

Hard castors with unloaded brakes: Ø50 mm, PA (Nylon) Type 6 and PUR. Black (RAL 9005) and grey (RAL 7022). Hard castors will be locked when not in use.

Dimensions

FourSure® 66 Polypropylene shell w. gas




FourSure® 66 Seat pad w. gas



FourSure® 66 Inside upholstery w. gas



FourSure® 66 Fully upholstery w. gas



Environmental data

Product environmental data can assist you in meeting the requirements for LEED, BREEAM, WELL, and SKA building

FOURSURE 66 PP SHELL



RECYCLED CONTENT

RECYCLABILITY

100%

CARBON FOOTPRINT

Kg CO₂e per unit

MATERIAL BREAKDOWN



FOURSURE 66 PP SHELL SEAT PAD



RECYCLED CONTENT

RECYCLABILITY

93%

CARBON FOOTPRINT

Kg CO₂e per unit

MATERIAL BREAKDOWN



FOURSURE 66 PP SHELL INNER UPHOLSTERED



RECYCLED CONTENT

RECYCLABILITY

90%

CARBON FOOTPRINT

Kg CO₂e per unit

MATERIAL BREAKDOWN



FOURSURE 66 PP SHELL FULLY UPHOLSTERED



RECYCLED CONTENT

RECYCLABILITY

96%

CARBON FOOTPRINT

Kg CO₂e per unit

MATERIAL BREAKDOWN





CARBON FOOTPRINT

The carbon footprint (CO_2e) covers the full product life cycle, cradle-to-grave. Calculations follow the Product Environmental Footprint (PEF) methodology and are obtained using the MALBAR screening tool.



UPHOLSTERY

Please note that fabric is not included in the above figures.



Quality and environment

At Ocee & Four Design, we care about sustainability. We strive to reduce our impact by producing quality furniture in a sustainable manner. Find out more about our journey on Oceefour.com 7

COMPANY CERTIFICATIONS

ISO 9001 ISO 14001 FSC Chain of Custody (License Code: FSC-C161956) FISP Full Membership

WARRANTY

Ocee & Four Design provides a 5-year warranty on all products within our price list. This warranty covers breakage and damage of products occurring because of deficient craftsmanship performance under normal use. The warranty shall lapse if the product shows signs of mishandling abuse or other physical damage. The warranty does not cover those parts of the product which are exposed to abrasion during use.

INSTRUCTIONS

Assembly instructions can be found at our website.

MAINTENANCE

Refer to our Maintenance Guide 7

DISASSEMBLY & RECYCLING

Products should be disassembled and separated into their components and materials before recycling. Most products can be disassembled using hand tools. Metal parts are commonly recycled. Powder coated frames are treated with a paint classified as not dangerous according to directive 1999/45/EF. Wood can either be recycled or incinerated. Plastic shells can be recycled. Upholstery and veneer shells are not recyclable but can be disposed of through incineration. Processes for recycling vary so check with your waste management organisation.

